

SAFETY DATA SHEET

SECTION 1. Identification of the Substance and Manufacturer

Product: **CHEM COPP 75%**
Copper (II) Oxide

Common uses: Industrial Chemicals

Manufacturer: American Chemet Corporation www.chemet.com
145 HWY 282 / P.O. Box 1160
East Helena, MT 59635 U.S.A.
+1(406) 227-5302 (Phone) +1(406) 227-8047 (Fax)

24-Hour Emergency: 3E Company

American Chemet Corporation/3E Company **Global Incident Response Access Code: 334129**
American Chemet Corporation/3E Company **Contract Number 14862**

Americas	Europe	Asia Pacific	Middle East/Africa
1-866-519-4752 (US, Canada, Mexico) or 1-760-476-3962	1-760-476-3961	1-760-476-3960	1-760-476-3959

Local Contact (if Applicable):

SECTION 2. Hazard Identification

Classification System:

The classification is based on the criteria in the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

GHS Label Elements



Warning

Very toxic to aquatic life with long lasting effects.
Aquatic Acute, Category 1. Aquatic Chronic, Category 1.
M = 1

GHS Hazard Statements:

H410 – Very toxic to aquatic life with long lasting effects.
H412 - Harmful to aquatic life with long lasting effects.

GHS Precautionary Statements:

P273: Avoid release to the environment.
P391 – Collect spillage.
P501 – Dispose of contents/container in accordance with local/national/international regulations

SECTION 3. Composition/Information of Ingredients

Ingredient	%	CAS No.
Cupric Oxide	91%	1317-38-0
Cuprous Oxide	3%	1317-39-1
Talc	5.5%	14807-96-6

SECTION 4. First Aid Measures

INHALATION: Remove to fresh air. Lay patient down. Cover with blanket.
INGESTION: Give 200-300 mL water to drink. DO NOT induce vomiting.
SKIN CONTACT: For skin exposure, remove contaminated clothing and wash with soap and water.
EYE CONTACT: If irritated, flush eyes and skin with large volumes of fresh water for 15 minutes.
MEDICAL NOTES: If any adverse symptoms persist seek immediate medical attention.

SECTION 5. Fire-Fighting Measures

Extinguishing Media: CO₂, ABC extinguisher, or water spray.
Special Fire Fighting Procedures: Material is non-flammable. Use firefighting measures appropriate to surrounding materials.
Special Exposure Hazards: Cuprous oxide is stable in dry air, but can oxidize to cupric oxide in the presence of moist air at temperatures above 100°C.
Additional Information: Collect contaminated fire fighting water separately. It must not enter the sewer system.
Personal Protective Equipment: Wear self-contained breathing apparatus.

SECTION 6. Accidental Release Measures

Personal Precautions:	Spilled material may produce dust hazard if not handled correctly. Wear appropriate personal protective equipment: coveralls, gloves & eye protection.
Environmental Precautions:	Do not allow to enter drains or watercourses. If the product enters drains or sewers, immediately inform the local water company. Where there is contamination of streams, rivers or lakes, contact local agency with responsibility for the environment.
Methods for Clean Up:	Contain spillages and clean up with vacuum or conventional tools and attempt to minimize dusting. Place in a suitable container for recycling or disposal in accordance with local and national waste regulations.

SECTION 7. Handling and Storage

Handling:	Only use in a well-ventilated area and prevent the creation of dusts. If concentrations exceed the occupational exposure limits, use suitable respiratory protection.
Storage:	Store in a cool, dry, well-ventilated place. Keep away from food, drink and animal feeding stuffs. Keep containers sealed.
Common uses:	Industrial chemicals

SECTION 8. Exposure Controls/Personal Protection

Occupational Exposure Standards:	Copper as dusts & mist : OSHA PEL & ACGIH TLV 1 mg/m ³ 8-hour TWA
Occupational Exposure Controls:	All personal protective equipment, including respiratory equipment, used to control exposure to hazardous substances must be selected to meet the requirements of national personal protective equipment regulations.
Personal Protection:	
Ventilation:	To keep below the U.S.A. OSHA and EU exposure limits, use general dilution type ventilation.
Respiratory Protection:	Cartridge type particulate filter respirator or dust-mask conforming to U.S.A. NIOSH. Refer to Respiratory Protective Devices approved by NIOSH under 42 CFR 84 and the appropriate European standard.
	
Hand Protection:	Wear if skin contact is probable and skin is sensitive.
	
Eye Protection:	Safety glasses or goggles.
Skin Protection:	Long sleeve shirt(s) if contact is probable and skin is sensitive.
Environmental Protection:	Do not allow to enter drains or watercourses.

SECTION 9. Physical and Chemical Properties

Appearance:	Black Fine Powder	Vapor Pressure:	NA
Odour:	None	Vapour Density:	NA
Boiling Point:	NA	Melting Point:	1326 °C
Evaporation Rate:	NA	Solubility in Water:	Negligible(<0.1%)
Specific Gravity(H ₂ O=1)	6.4	Percent Volatile (v/v)	0%

SECTION 10. Stability and Reactivity

Stable X Unstable _____

Conditions & Materials to Avoid:

- Temperatures above 100 °C while in the presence of moist air.
- Under certain conditions CuO may react violently with strong reactants such as acids and bases.

Hazardous Decomposition Products: Copper fumes will be released if heated above its melting point (1326 °C).

Hazardous Polymerization: Will Not Occur

SECTION 11. Toxicological Information

Acute Toxicity		Skin Irritation:	Not classified as a skin irritant
Oral (Rat):	Not classified	Eye Irritation:	Not classified as an eye irritant
Dermal (Rabbit):	Not classified	Sensitization:	Not classified as a dermal sensitizer
Inhalation (Rat):	Not classified		

SECTION 12. Ecological Information

Toxic to fish and other aquatic organisms.

Prevent from entering drains, sewers, and surface water.

SECTION 13. Disposal Considerations

PACKAGING:	Dispose of in accordance with procedures applying to the disposal of the product.
PRODUCT:	Dispose of surplus and contaminated materials (including sawdust) at an approved landfill or in accordance with other national or regional provisions.

European Waste Catalogue:

06 11 99	Wastes not otherwise classified
----------	---------------------------------

SECTION 14. Transportation Information

US DOT: Not Regulated. Class 9 materials do not require placarding for U.S.A. ground transport (49 CFR 172.504(f)(9)). *Exceptions*, except when all or part of the transportation is by vessel, the requirements specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicle, rail car, or aircraft (49 CFR 171.4(c)). Permissive labelling is allowed by U.S.A. DOT (49 CFR 172.401(c)).

Proper Shipping Name: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (copper oxide), Class 9, PG III, MARINE POLLUTANT

. Land transport ADR/RID (cross-border) Excluding U.S.A. Ground Transport



- **ADR/RID class:** 9 (M7) Miscellaneous dangerous substances and articles
- **Danger code (Kemler):** 90
- **UN Number:** 3077
- **Packaging group:** III
- **Hazard label:** 9
- **Proper shipping name:** 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (copper oxide)
- **Tunnel Restriction Code:** E

. Maritime transport IMDG:



- **IMDG Class:** 9
- **UN Number:** 3077
- **Hazard Label:** 9
- **Packaging group:** III
- **Marine pollutant:** yes
- **Proper shipping name:** 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (copper oxide)
- **EmS Code:** F-A, S-F

. Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 9
- **UN/ID Number:** 3077
- **Hazard Label:** 9
- **Packaging group:** III
- **Proper shipping name:** 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (copper oxide)

SECTION 15. Regulatory Information

U.S. EPA EPCRA Section 313 Reportable Product – (contains copper)
U.S. EPA Reportable Quantity: 5,000 lbs. (2,270 kg)

REACH Registration Number for American Chemet Corporation's Cupric Oxide: 05-2114625702-54-0000

SECTION 16. Other Information

Keep out of reach of children. Read and follow all label instructions. This information is based on our present knowledge. However, this is not a guarantee of specific product features. It is the user's responsibility to satisfy themselves as to the suitability and completeness of this information for their own particular use.

Country Specific 24-Hour Emergency Phone Numbers: 3E Company

Country	Number	Languages
Australia	+61 1 800 686 951	English
China	+86 4001 2001 74	Chinese
New Zealand	+64 800 451719	English
United Kingdom	+44 8 08 189 0979	English